



# BATTERY TENDER® WATERPROOF 800 INTERNATIONAL 12 VOLT 800 mAmp

## WATERPROOF

### Single Output 12 Volt Battery Charger

Note: This unit is operated and performs exactly like the Battery Tender® Junior single output unit. The only difference is that the DC output current is higher at 800 mA compared to 750 mA, and the AC input is universal.

- ❖ “SUPER SMART™” TECHNOLOGY
- ❖ SPARK PROOF
- ❖ SHORT CIRCUIT PROTECTED
- ❖ REVERSE POLARITY PROTECTED
- ❖ WATERPROOF
- ❖ 3-Step Charging (Qualification, Bulk, & Float Maintenance)
- ❖ WEIGHS ONLY 1 POUND (1.2 LBS. With Power Cords)
- ❖ 3 YEAR WARRANTY

TECHNICAL SPECIFICATION SUMMARY		
Input Voltage & Frequency		100 to 240 VAC, 50/60 Hz
DC OUTPUT		
Output Current	Bulk Charge	800 mADC Constant
Output Voltage	Absorption Charge Peak	14.4 VDC Maximum
	Maintenance Charge	13.2 VDC Constant
Operating Temperature		-20 °C to +50 °C
DIMENSIONS & WEIGHT		
Charger Case Dimensions (Without Input & Output Cords)	4.2 in (107 mm) L x 2.75 in (70 mm) W x 1.4 in (36 mm) H Allow an additional 1 in (25.4 mm) on each end of the length dimension for safe bend of AC and DC power cord strain relief.	
Shipping Box	Approx: 10.75 in (273 mm) L x 10.75 in (273 mm) W x 3.75 in (95 mm) H	
TYPICAL SHIPPING WEIGHT	WITH: ALLIGATOR CLIPS & FUSED RING TERMINAL CABLES in CLAMSHELL PACKAGING	2.5 lb (1.14 kg)

**AVAILABLE NOW !!**

CONFIGURATION & PRICING INFORMATION	
Deltran PART NO.	COUNTRY / REGION
022-0150-DL-EU	CONTINENTAL EUROPE
022-0150-DL-UK	ENGLAND / IRELAND
022-0150-DL-WH	WESTERN HEMISPHERE: N & S AMERICA
081-0148-25	Optional 25 ft Extension Leads, MSRP: \$9.95 U.S.D.
<b>MSRP: \$49.95 U.S.D.</b>	

# BATTERY TENDER® WATERPROOF 800



**AVAILABLE NOW !!**

## DELTRAN CORPORATION

801 International Speedway Blvd.  
DeLand, Florida 32724  
Phone 386-736-7900 FAX 386-736-0379  
[www.batterytender.com](http://www.batterytender.com)

Effective December 11, 2003