



# RT 6120 (6V12.0Ah)

RT6120 is a general purpose battery with 5 years life in standby service, or more than 260 cycles at 100% D.O.D by cyclic use. As with all Ritar batteries, all RT models are rechargeable, highly efficient, leak proof and maintenance free.




## Specification

<b>Cells Per Unit</b>	3
<b>Voltage Per Unit</b>	6
<b>Capacity</b>	12.0Ah @20hr-rate to 1.75V per cell @25°C
<b>Weight</b>	Approx. 1.8 Kg
<b>Max. Discharge Current</b>	120 A (5 sec)
<b>Internal Resistance</b>	Approx. 8 mΩ
<b>Operating Temperature Range</b>	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
<b>Normal Operating Temperature Range</b>	25°C±5°C
<b>Float charging Voltage</b>	6.8 to 6.9 VDC/unit Average at 25°C
<b>Recommended Maximum Charging Current Limit</b>	3.6A
<b>Equalization and Cycle Service</b>	7.25 to 7.45 VDC/unit Average at 25°C
<b>Self Discharge</b>	RITAR batteries can be stored for more than 6 months at 25°C. Please charge batteries before using. For higher temperature, the time interval will be shorter.
<b>Terminal</b>	Faston Tab 187(F1)/Faston tab 250(F2)
<b>Container Material</b>	A.B.S. (UL94-HB) Flammability resistance of UL94-V2 can be available upon request.



## Dimensions



### Constant Current Discharge Characteristics Unit: A(25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	49.8	33.3	25.6	14.1	8.33	4.99	3.07	2.52	2.03	1.49	1.18	0.66
1.67V	46.6	31.1	24.1	13.9	8.28	4.96	3.06	2.51	2.02	1.49	1.16	0.64
1.70V	44.1	30.1	23.5	13.8	8.22	4.94	3.05	2.50	2.00	1.49	1.15	0.62
1.75V	39.8	28.2	22.3	13.4	8.10	4.88	3.04	2.48	1.99	1.49	1.14	0.60
1.80V	35.6	26.3	21.0	13.1	7.98	4.80	3.01	2.47	1.98	1.48	1.12	0.58
1.85V	31.4	24.3	19.8	12.8	7.87	4.73	2.99	2.46	1.97	1.48	1.10	0.56

### Constant Power Discharge Characteristics Unit: W(25°C)

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	96.0	62.4	50.7	28.2	16.6	9.97	6.13	5.02	4.76	2.99	2.34	1.31
1.67V	90.0	60.0	48.1	27.7	16.6	9.91	6.12	5.00	4.73	2.99	2.32	1.26
1.70V	88.2	58.2	47.0	27.5	16.6	9.89	6.11	5.00	4.72	2.96	2.29	1.24
1.75V	79.7	55.8	44.6	26.9	16.3	9.73	6.07	4.97	4.70	2.95	2.27	1.19
1.80V	71.2	52.2	42.1	26.2	16.0	9.60	6.02	4.93	4.69	2.94	2.23	1.15
1.85V	62.7	48.6	39.6	25.6	15.7	9.46	5.98	4.90	4.68	2.94	2.20	1.12


All mentioned values are average values.

# RT 6120


# 6V12.0Ah




## Temperature effects curve




## Storage characteristic




## Life characteristics of cyclic use




## Effect of temperature on long term float life



## Charge characteristic Curve for standby use



## Discharge characteristic Curve



## Charging Procedures

Application	Charge Voltage (V)			Max. Charge Current
	Temperature	Set point	Allowable range	
Cycle Use	25°C	14.7	14.4~15.0	0.3C
Standby	25°C	13.7	13.6~13.8	0.3C

## Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/cell	1.75V	1.70V	1.60V
Discharge Current (A)	(A) ≤ 0.2C	0.2C < (A) < 1.0C	(A) ≥ 1.0C

## Charging Procedures(6V series)

Application	Charge Voltage (V)			Max. Charge Current
	Temperature	Set point	Allowable range	
Cycle Use	25°C	7.35	7.25~7.45	0.3C
Standby	25°C	6.85	6.8~6.9	0.3C

**Charge the batteries at least once every six months, if they are stored at 25°C.**

Charging Method:

Constant Voltage	7.25~7.45V, 5~11h, Max. Current 0.1CA
Constant Current	0.1CA×5h
Fast	0.3CA×1.7h

## SHEN ZHEN RITAR POWER CO.,LTD.

Room 405, Tower C, Huahan Building, Langshan Road 16, North High-tech Industrial Park, Nanshan District, Shenzhen, 518057, China  
 URL: [www.ritarpower.com](http://www.ritarpower.com) Tel: +86-755-33981668 Fax: +86-755-83475180